

Low-voltage Battery RL Series

iBAT-R-5.12L



High Performance

LFP battery cell, safe and reliable
24-hour standby power, worry free in case of blackout
Single battery 5.12kWh, expandable to 30.72kWh



Economic & Intelligent

Self-use PV generation to reduce carbon emissions
Daytime charge and discharge at night to save electricity bill



Easy to Install

Plug and play, easy to install
Stackable battery packs, flexible expansion of standby power

Type		iBAT-R-5.12L				
Battery Type	LFP					
Cell Capacity	100Ah					
Battery Capacity	5.12kWh					
Expandable Capacity	10.24kWh	15.36kWh	20.48kWh	25.6kWh	30.72kWh	
Battery Number	2 pcs	3 pcs	4 pcs	5 pcs	6 pcs	
Dimensions(L×W×H mm)	678×310×571	678×310×822	678×310×1073	678×310×1324	678×310×1575	
Weight	123kg	178kg	233kg	288kg	343kg	
DOD	93%					
Rated Voltage	51.2V					
Voltage Range	43.2~57.6V					
Continuous charge/discharge current ^[1]	50A					
Max. charge/discharge current ^[1]	100A					
Battery Weight	55kg					
Battery Dimensions(L×W×H)	678×310×251mm					
Communication	CAN,485					
Operation Temperature	-10°C~55°C					
Storage Temperature	-20°C~55°C					
Humidity	≤95%(no condensing)					
Altitude	<2000m					
Ingress Protection	IP65					
Cooling	Natural					
Cycle Life	≥6000 ^[2]					
Safety Standards	CE, UN38.3, SDS, IEC62619					

[1] The current is affected by temperature and SOC.

[2] Test conditions: temperature 25±2°C , charge & discharge current 0.5C/0.5C, 70%EOL≥6000

Contact us:
Shanghai Hoenergy Power Technology Co.,Ltd
Tel: +86 152 2195 1952
Email: info@hoenergy.com.cn
Website: www.hoenergypower.com

